



H07V-K (RK) 450/750V

Area, mm ²	1.5	2.5	4	6	10	16	25	35	50
Antal trådar.....	32	54	48	72	72	112	176	248	352
Tråddiameter, nom.....	0.23	0.23	0.31	0.31	0.41	0.41	0.41	0.41	0.41
Ledardiameter, nom.....	1.6	2.1	2.5	3.2	4.2	5.3	6.5	7.5	9.0
Ledarresistans, Max ohm/km.....	13.3	7.98	4.95	3.30	1.91	1.21	0.78	0.554	0.386
Isoleringstjocklek, nom.....	0.7	0.8	0.8	0.8	1.0	1.0	1.2	1.2	1.4
Isoleringstjocklek, min.....	0.53	0.62	0.62	0.62	0.8	0.8	0.98	0.98	1.16
Ytterdiameter, nom.....	3.0	3.7	4.1	4.8	6.2	7.3	8.9	9.9	11.8
Vikt, kg/km.....	20	32	45	65	110	170	250	340	480

Area, mm ²	70	95	120	150	185	240	300	400
Ledardiameter, nom.....	10.8	12.3	14.7	16.7	18.7	21.3	24	27.4
Ledarresistans, Max ohm/km.....	0.272	0.206	0.161	0.129	0.106	0.0801	0.0641	0.0486
Isoleringstjocklek, nom.....	1.4	1.6	1.6	1.8	2.0	2.2	2.4	2.6
Isoleringstjocklek, min.....	1.16	1.34	1.34	1.52	1.7	1.88	2.06	2.24
Ytterdiameter, nom.....	13.6	15.5	17.9	21.0	22.6	26.7	28.8	32.6
Vikt, kg/km.....	660	875	1110	1400	1700	2230	2750	3650